SLINEX

Design. Uniqueness. Innovations

IP outdoor panel

Facy

Facy IP outdoor panel provides convenient premises access for a large number of people. Assign unique face ID, MIFARE IC proximity cards to the panel's internal memory. Thus, users will be able to safely open the door using a unique wireless key, user code or face recognition.

CAMERA SENSOR	1/3" CMOS, 2.0 MP	**POWER**	15 V from external power supply or PoE
BACKLIGHT	IR LED, up to 1.5 m		
VIEWING ANGLE	140°	**CONSUMPTION**	Up to 10 W
SCREEN	10" color TFT	**LOCK TYPE**	Mechanical or magnetic, up to 2 A current
RESOLUTION	1024×600 pixels		
BODY STRUCTURE	Aluminum + acrylic glass	**BUTTONS**	Capacitive touch screen
PROTECTION CLASS	IP65	**INSTALLATION TYPE**	Flush mount
DIMENSIONS	190×340×38 mm	**TEMPERATURE RANGE**	-40 ... +50 ˚C
COLOR	Black+silver	**ACCESS CONTROL**	MIFARE IC cards, user codes or face recognition

Unique features

Access control
Use Mifare IC wireless cards, key code or face ID to unlock the door

Touch screen
Capacitive touch screen provides the best experience

Viewing angle
140°

POE support
No need to use additional power cable

Product page