



IP outdoor panel

Ling

Ling series is the multi apartment outdoor panels with an ultramodern design. Panels has a lot of advantages, among them are 2MP color camera, built-in Mifare card reader, mechanical IR-cut filter, nameplates backlight. This series of panels has different options of buttons quantity, from 6 up to 32 users.

CAMERA RESOLUTION	2MP	POWER	PoE or 12-15 V from ext. power supply
NIGHT BACKLIGHT	IR LED, up to 1.5 m	CONSUMPTION	Up to 30 W
SENSOR TYPE	1/3" CMOS	LOCK TYPE	Mechanical or magnetic, up to 2 A current
VIEWING ANGLE	120°	CALL BUTTONS	Mechanical
MIN. ILLUMINATION	0,01 Lux	INSTALLATION TYPE	Flush mount
BODY STRUCTURE	Metal alloy	COLORS	Grey (aluminum).
ACCESS CONTROL	Mifare IC cards (1000 pcs.)	TEMPERATURE RANGE	-40 ... +50 °C
PROTECTION CLASS	IP65	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
DIMENSIONS	130×253×45 mm (S size) 130×376×45 mm (L size)		

Unique features



Operating temperature
-40 – +50 °C



IR cut filter
Improves image quality both in daylight and dark conditions



Viewing angle
120°



Mifare IC cards
Up to 1000 IC cards can be added to the panel memory



Product page